

k1m0ch1

Practical Security Engineer

by ■ positive technologies

Automating Pentests with AI and MCP

```
def key_pressed(key):  
    print(f"{key} pressed")
```

```
# Create the main window  
root = tk.Tk()  
root.title("Simple Keyboard")
```

- ykw, somehow it feels wrong, but you need to know about this.

positive
Jakarta hack
talks

#PHTalks

```
# Create buttons for keys  
keys = ['Q', 'W', 'E', 'R', 'T', 'Y', 'U', 'I', 'O', 'P']  
in the following keys:  
    button = tk.Button(root, text=key, width=5,  
        command=lambda k=key: key_pressed(k))  
    button.pack(side=tk.LEFT)
```



k1m0ch1 a.k.a Yahya F. Alfatih



I am Yahya F. Alfatih
aka k1m0ch1
aka 0r4ng324n3h
aka BukanYahya
aka FuckingA

 @BukanYahya

 @k1m0ch1

DayJob as SWE that could handle the
Infrastructure and Offensive Security

NightJob doing defensive at some public
service such as saweria and some gov
site

!!Disclaimer!!

- This presentation is created solely for **educational and research purposes**. It is not intended to promote or support any unauthorized or unethical activities.
- The author is not liable for any misuse, harm, or legal consequences resulting from actions taken based on the content shared in this presentation.
- All demonstrations were conducted in a controlled environment with full authorization. Replicating them without permission may violate legal or ethical standards
- Do not apply these methods without **proper authorization**
- Unauthorized testing may be **illegal** and carry serious consequences
- Use this knowledge **ethically and responsibly**



01

by ■ positive technologies

```
def key_pressed(key):  
    print(f"{key} pressed")
```

```
# Run the application  
root.mainloop()
```

Evolution of Hacking

```
# Create buttons for keys  
keys = ['Q', 'W', 'E', 'R', 'T', 'Y', 'U', 'I', 'O', 'P']  
in the following keys:  
    button = tk.Button(root, text=key, width=5,  
        command=lambda k=key: key_pressed(k))  
    button.pack(side=tk.LEFT)
```






#PHTalks

Hacking Through the year

Hacking in '80-'90

Hacking in '00-'20

Hacking now



Does AI will replace the cybersecurity ? 🤔

↑ Confused in choosing AI or Cybersecurity (self.learnprogramming)
• submitted an hour ago by Anonymous ↩
↓

I'm doing 4 year engineering degree in computer science (India) and now I'm in second year i have to choose any specialization, I'm now confused in choosing AI and cybersecurity, which would be the best choice? I have interest in both the fields, I'm just insecure about job (actually the entry level) in cybersecurity, and will AI replace cybersecurity?? Can someone please help me...

4 comments source share save hide report crosspost hide all child comments

all 4 comments navigate by ▾
sorted by: best ▾

B *I* S ^{A²} ∞ “ <> ⋮ ⋮ ⋮ 10/10000



DariuslsLove • 1mo ago



If we knew the answer to this question with certainty, we would all be multi-millionaires.

I would assume that you will use AI as a tool in cybersecurity in the future, but there would probably still be human elements overlooking things.

Asymmetric Rule == more Difficulty for AI

Offensive Defensive

- | | | |
|-------------------------------|---|--|
| you only need to got one hole | - | you need to protect and set rule for everything |
| single entry = win | - | No entry at all = win |
| Low to Mid Cost of failure | - | High Cost of failure (breach, data loss, reputation) |
| Fast and aggressive | - | slower and reactive |



Internet Traffic and population

- What the fuck are they actually doing

```
def key_pressed(key):  
    print(f"{key} pressed")
```

```
# Run the application  
root.mainloop()
```

```
# Create buttons for keys  
keys = ['Q', 'W', 'E', 'R', 'T', 'Y', 'U', 'I', 'O', 'P']  
in the following keys:  
    button = tk.Button(root, text=key, width=5,  
        command=lambda k=key: key_pressed(k))  
    button.pack(side=tk.LEFT)
```



#PHTalks


The Scale of the Internet = The Scale of the Risk

8.1 billion people on earth, but over 30+ billion connected devices <https://www.statista.com/statistics/1101442/iot-number-of-connected-devices-worldwide/>

That's an average of nearly 4 devices per person and growing

5.56 billion people (67.9%) are online as of 2025 <https://datareportal.com/reports/digital-2025-global-overview-report>


Global internet traffic by year



Source: 2025 Imperva Bad Bot Report

Half the Internet Isn't Human

- Bots now make up ~50% of all internet traffic
Source: [Imperva 2024 Bot Report](#)
- Over 30% are “bad bots” — used for scanning, exploiting, brute-forcing, and data scraping
Source: [Akamai Bot Analysis 2024](#)
- Many are powered by AI, using LLMs to bypass CAPTCHAs and generate adaptive attacks



Workspace 1 Mozilla Firefox

Attackers Outpace Defenders

- **Average time for attackers to exploit new vulnerabilities: 5 days** in 2023
Source: Google Cloud research
[patentpc.com+7cyberdefensemagazine.com+7tuskira.ai+7extrahop.com+13welivesecurity.com+13techtarg](#)
- **Time for IT teams to patch critical flaws: up to 3 weeks** (28 days) on average
Source: Synopsys survey, via Axios [axios.com+1computerweekly.com+1](#)
- **Attack timeline vs. defense cycles:**
 - Exploit in under a week
 - Patch in multiple weeks
- **This gap is a goldmine for attackers**, especially when using AI to automate discovery, exploitation, and weaponization.

AI & Pentest Automation

- What the fuck are they actually doing

```
def key_pressed(key):  
    print(f"{key} pressed")
```




```
# Run the application  
root.mainloop()
```

```
# Create buttons for keys  
keys = ['Q', 'W', 'E', 'R', 'T', 'Y', 'U', 'I', 'O', 'P']  
in the following keys:  
    button = tk.Button(root, text=key, width=5,  
        command=lambda k=key: key_pressed(k))  
    button.pack(side=tk.LEFT)
```



#PHTalks

Evolution of Automation



WIY

AI Agentic Pentest

Dimi Trizna @ditrizna · May 15
🤖👾 Unbelievable, **Agentic** AI System is Highest Ranking in HackerOne Leaderboard

Honestly, I still struggle to accept it. #1 ranking member in HackerOne VDP Leaderboard [1] in the past 3 months, is **agentic** AI system from **@Xbow**.

HackerOne Leaderboard

All leaderboards are based on the selected time period.

BBP VDP All

Highest Reputation

Ranking is calculated based on reputation earned.

		Reputation	Signal ⓘ
1.	 xbow	804	6.70
2.	 arielrachamim	744	6.89
3.	 almuntadhar	590	6.86
4.	 2026	526	6.41
5.	 0x_z5zf	476	7.00


XBOW (xbow)
<https://www.xbow.com>


Joined August 2024



Stats

All Time ▾

6.74
Signal

88th
Percentile

18.01
Impact

85th
Percentile

7100
Reputation

-
Rank

Still needs humans for:

- Target scoping
- Business logic validation
- Complex exploit decisions

Credits

202

Vulnerabilities found

202

Thanks received

Why AI is Revolutionizing Pentesting

- **From Manual to Autonomous**

Traditional pentests involved scripts and hours of manual recon.

- **Real world Impact**

- AI agent **XBOW** submitted 1,000+ bugs on HackerOne
- Detected 54 Critical, 242 High issues — fully automated


- **Advantages**

Works 24/7

Scales to thousands of endpoints

Finds common misconfigs fast

- **The Catch?**



The Future of Pentesting is AI-Augmented

- **AI is not replacing pentesters it's becoming their sidekick.**
- AI handles:
 - Recon & fingerprinting
 - Exploit generation & testing
 - Report drafting & deduplication
- Humans handle:
 - Prioritization
 - Business impact
 - Creative chaining & logic abuse

```
def key_pressed(key):  
    print(f"{key} pressed")
```

```
# Run the application  
root.mainloop()
```

Model Context Protocol

```
# Create buttons for keys  
keys = ['Q', 'W', 'E', 'R', 'T', 'Y', 'U', 'I', 'O', 'P']  
in the following keys:  
    button = tk.Button(root, text=key, width=5,  
        command=lambda k=key: key_pressed(k))  
    button.pack(side=tk.LEFT)
```



#PHTalks


What is MCP ?

MCP = Model Context Protocol


A protocol that lets LLMs **interact with external tools, APIs, and environments** like a developer or agent.

Instead of relying on static prompts, MCP gives the model **a working environment with access to tools like:**


- Shells
- Web browsers
- Exploit runners
- File systems



What is MCP ?



VS.



MCP Architecture




Fig. 2. The workflow of MCP.

What it look like MCP working ?

Vibe Hacking

```
def key_pressed(key):  
    print(f"{key} pressed")
```

```
# Run the application  
root.mainloop()
```

■ you wat ?

```
# Create buttons for keys  
keys = ['Q', 'W', 'E', 'R', 'T', 'Y', 'U', 'I', 'O', 'P']  
in the following keys:  
    button = tk.Button(root, text=key, width=5,  
        command=lambda k=key: key_pressed(k))  
    button.pack(side=tk.LEFT)
```




#PHTalks

Scenario & Goal


- I will define my target
- I will store the information & finding to google sheet
- I will connect my MCP Client to most common hacking tools
- I'm not going to do some offensive hacking here
- just do some basic scanning with recon tools
- and nuclei will do



Oversimplified Flow Pentest



This Scenario Pentest



What I will use

- Claude Desktop
- nmap MCP server
- playwright MCP
- shodan mcp
- webscanner mcp
- google-sheet mcp



in Action



Prompt



Key Difference MCP vs AI Agentic

Aspect	MCP (Model Context Protocol)	AI Agentic
Definition	A protocol that manages <i>structured and controlled context flow</i> between user, task, and model.	A system where AI operates as an <i>autonomous agent</i> , making decisions based on goals, environment, and memory.
Autonomy	Not autonomous; context is explicitly provided and controlled by user or system logic.	Autonomous; the agent can plan, act, observe, and revise goals without human intervention.
Execution Model	Stateless or session-based, following strict prompts and external context provisioning.	Stateful; maintains internal memory, long-term objectives, and ongoing reasoning loops.
Use Case	Ideal for repeatable, structured, and security-sensitive workflows (e.g., pentesting via secure pipelines).	Better for exploration, dynamic environments, and multi-step task solving (e.g., autonomous coding assistants).
Typical Application	Secure APIs, sensitive LLM ops, red team automation.	AI copilots, research agents, creative assistants.

Thanks to

- my wife
- Rin & Zeihan
- PT Team

and tribute for



Arief Wicaksono

Iwan Sumantri

positive Jakarta hack talks

Thank you




HATUR NUHUN
ꦲꦠꦸꦫꦤꦸꦃꦸꦤ

#PHTalks

by ■ positive technologies

```
def key_pressed(key):  
    print(f"{key} pressed")
```



```
# Create the main window  
root = tk.Tk()  
root.title("Simple Keyboard")
```

```
# Create buttons for keys  
keys = ['Q', 'W', 'E', 'R', 'T', 'Y', 'U', 'I', 'O', 'P']  
in the following keys:  
    button = tk.Button(root, text=key, width=5,  
        command=lambda k=key: key_pressed(k))  
    button.pack(side=tk.LEFT)
```